

In the claims:

Please cancel claim 1 without prejudice or disclaimer and substitute in lieu thereof claim 23 as follows:

1 23. (new) A coating thickness measuring instrument having a first mode of
2 operation in which the instrument is operative to make measurements with a first resolution
3 and a second mode of operation in which the instrument is operative to make measurements
4 with a second resolution, the first resolution being greater than the second resolution, the
5 instrument comprising:
6 an inductive probe comprising a drive coil and a pick-up coil;
7 a means for driving an alternating current in the drive coil;
8 a means for detecting the output of the pick-up coil;
9 a means for modifying the amplitude of the current in the drive coil in dependence
10 upon the output of the pick-up coil; and
11 a switch to enable the means for modifying the amplitude of the current in the
12 drive coil to be switched in and out of operation, in order to switch the instrument between the
13 first and second modes.

Please amend the following claims as indicated:

1 2. (Amended Once) The instrument of claim [1] 23, wherein when the instrument
2 is in the first mode, the instrument is operative to make measurements in a first range and
3 when the instrument is in the second mode, the instrument is operative to make measurements
4 in a second range.

1 3. (Amended Once) The instrument of claim [1] 23, wherein when the instrument is
2 in the first mode, the instrument is operative to make measurements in a first range at a high
3 resolution and when the instrument is in the second mode, the instrument is operative to make
4 measurements in a second range at a lower resolution, the second range being longer than the
5 first range.

1 4. (Amended Once) The instrument of claim [1] 23, wherein when the instrument is
2 in the first mode, the instrument is operative to make measurements in a first range and when
3 the instrument is in the second mode, the instrument is operative to make measurements in a
4 second range, such that the first range and the second range overlap.

1 5. (Amended Once) The instrument of claim [1] 23, [further including an] wherein
2 the inductive probe [comprising a drive coil, and] comprises two pickup coils.

1 6. (Amended Once) The instrument of claim [1] 23, [further including an] wherein
2 the inductive probe [comprising a drive coil and] comprises two pickup coils; and the means
3 for driving an alternating current in the drive coil is arranged to [a means to] drive an
4 alternating current of substantially constant amplitude in the drive coil.

1 7. (Amended Once) The instrument of claim [1] 23, [further including:
2 an inductive probe comprising a drive coil and two pickup coils; and
3 a means to drive an alternating current of substantially constant amplitude in the
4 drive coil;]
5 wherein the means [to drive] for driving an alternating current comprises an
6 oscillator and associated control loop circuit arranged to control the oscillator in dependence
7 upon current flowing in the drive coil.

1 8. (Amended Once) The instrument of claim [1] 23, further including:
2 [an inductive probe comprising a drive coil and two pickup coils; and
3 a means to drive an alternating current of substantially constant amplitude in the
4 drive coil; and]
5 a means for varying the amplitude of alternating current flowing in the drive coil;
6 and
7 wherein the means to drive an alternating current comprises an oscillator and
8 associated control loop circuit arranged to control the oscillator in dependence upon current
9 flowing in the drive coil.

1 9. (original) The instrument of claim 8, wherein the means for varying the amplitude
2 comprises a digitally controlled potentiometer.

1 10. (Amended Once) The instrument of claim [1] 23, [further including:
2 an] wherein the inductive probe [comprising a drive coil and] comprises two
3 pickup coils; and further including
4 a means for sensing variation in coupling between the drive and pickup coils and
5 converting the variation in coupling to a thickness value.

1 11. (Amended Once) The instrument of claim [1] 23, [further including:
2 an] wherein the inductive probe [comprising a drive coil and] comprises two
3 pickup coils; and further including
4 a means for sensing variation in coupling between the drive and pickup coils and
5 converting this to a thickness value;
6 wherein said means for sensing comprises a differential amplifier, means for
7 rectifying the output of the pickup coils and an analog to digital converter.

1 12. (Amended Once) The instrument of claim [1] 23, [further including:
2 an] wherein the inductive probe [comprising a drive coil and] comprises two
3 pickup coils; and further including
4 a means for sensing variation in coupling between the drive and pickup coils and
5 converting the variation in coupling to a thickness value, said means for sensing comprising a
6 differential amplifier, means for rectifying the output of the pickup coils and an analog to
7 digital converter;
8 wherein the means for rectifying comprises a synchronous detector controlled by a
9 synchronizing signal derived from the means to drive an alternating current in the drive coil.

Please cancel claim 13.

1 14. (Amended Once) The instrument of claim [1] 23, [further including:
2 an] wherein the inductive probe [comprising a drive coil and] comprises two
3 pickup coils; and
4 [a means to modify the amplitude of current flowing in the drive coil in
5 dependence upon output from the pickup coils;
6 wherein] the means to modify the amplitude comprises a control loop arranged to
7 reduce the amplitude of current supplied to the drive coil as differential output of the pickup
8 coils increases.

Please cancel claim 15.

1 16. (Amended Once) The instrument of claim [1] 23, comprising:
2 a microprocessor; and
3 a memory, the memory being operative to store look-up tables for both long and
4 short range modes of operation and the microprocessor being operative to generate a coating
5 thickness value using one of the look-up tables.

1 17. (Amended Twice) A coating thickness measuring instrument, comprising:
2 an inductive probe having a probe tip, a drive coil and a pickup coil;
3 a means for driving an alternating current in the drive coil;
4 a means for detecting the output of the pickup coil; and
5 a means for modifying the amplitude of the current in the drive coil in dependence
6 upon the output of the pickup coil, .

Please cancel claim 18 without prejudice or disclaimer and substitute in lieu thereof
claim 24 as follows:

1 24. (new) A coating thickness measuring instrument, comprising:
2 an inductive probe having a drive coil and a pickup coil;
3 a means for driving an alternating current in the drive coil;
4 a means for detecting the output of the pickup coil; and
5 a means for modifying the amplitude of the current in the drive coil in dependence
6 upon the output of the pickup coil, said modifying means comprising a control loop which is
7 switchable in and out of operation to provide two modes of operation for the instrument.

1 19. (Amended Once) The instrument of claim [18] 24, wherein the means for
2 modifying the amplitude of the current in the drive coil comprises a first control loop which is
3 switchable in and out of operation to provide two modes of operation for the instrument and
4 wherein the means for driving a current in the drive coil comprises a second control loop
5 arranged to maintain the amplitude of current in the drive coil at a substantially constant level.

 Please cancel claim 20 without prejudice or disclaimer and substitute in lieu thereof
claim 25 as follows:

1 25. (new) A coating thickness measuring instrument, comprising:
2 an inductive probe having a drive coil and a pickup coil;
3 a means for driving an alternating current in the drive coil;
4 a means for detecting the output of the pickup coil; and
5 a means for modifying the amplitude of the current in the drive coil in dependence
6 upon the output of the pickup coil, said modifying means comprising a first control loop
7 which is switchable in and out of operation to provide two modes of operation for the
8 instrument, and wherein the means for driving comprises an amplitude controlled oscillator,
9 and the first control loop is implemented by a current to voltage rectifier, a low pass filter and
10 an error amplifier.

1 21. (Amended Once) The instrument of claim [17] 25, wherein the means for
2 modifying is arranged to modify the input to the error amplifier and the amplitude of the
3 current in the drive coil.

1 22. (Amended Once) The instrument of claim [17] 24, wherein the means for
 detecting the output of the pickup coil comprises a synchronous detector.